

Technical Data Sheet

Product: DT029



THE EDGE
ON SAFETY

DESCRIPTION

We have designed this product to provide a low impact gradual transition between even height floorcoverings. The wide surface also provides a nice zone to protect the floorcovering edges. Suitable for high traffic flow areas internally and externally.

MATERIAL

T6 6063 Alloy aluminium - Natural Satin anodised.

Standard 2.5 Meter Lengths

13mm Insert.

Supplied pre drilled for countersunk screw fixing.

DIMENSIONS



EXAMPLE

In this example, DT024 has been installed for a smooth transition between same height vinyl and carpet. The profile uses slip resistant Tredsafe Diamondtred insert for safety, which meets standards of AS/NZS 3661.1:1991 and NZS 4586:2013.



For PDF and CAD drawings with full dimensions and installation guides, please refer to our website www.tredsafe.co.nz

Release: January 2019

Information given in this data sheet is based on the current state of knowledge. This does not exempt the purchaser from carrying out his own careful inspections of incoming goods and their suitability for local building codes. We reserve the right to make changes to the product data in the course of technical progress or due to operationally related further development. Owing to factors beyond our control during application, recommendations given in this data sheet require tests and experiments by the customer. Our recommendations do not exempt the customer from the obligation to check any infringements of third-party rights himself and eliminate them if necessary. The suggestions for product use are not equivalent to a warranty of its suitability for the recommended purpose.

Each new release of this data sheet supersedes the previous one.