Technical Data Sheet Product: **AA140**



DESCRIPTION

Natural Satin Anodised Aluminium minimal Stairnosing Profile. This stairnosing product has been designed as our most subtle stairnosing with a ramped edges to avoid trip hazards on uncovered stairs. Can also be used on ramps, decks or as a guidance strip in conjunction with our glowing insert. Suitable for interior and exterior uses.

MATERIAL

T6 6063 Alloy aluminium - Natural Satin anodised.


Standard 3.66 Metre Lengths.

1 x 13mm Tredsafe Insert.


Supplied pre drilled for countersunk screw fixing (screws

DIMENSIONS

EXAMPLE



In this installation, AA140 has been paired with AA139 on LVT covered stairs. This installation has used slip resistant Tredsafe
Diamondtred insert for safety, which meets standards of AS/NZS 3661.1:1991 and NZS 4586:2013. The safety white insert creates a contrast against the dark flooring to increase visibility.



For PDF and CAD drawings with full dimensions and installation guides, please refer to our website www.tredsafe.co.nz

Release: January 2019

Information given in this data sheet is based on the current state of knowledge. This does not exempt the purchaser from carrying out his own careful inspections of incoming goods and their suitability for local building codes. We reserve the right to make changes to the product data in the course of technical progress or due to operationally related further development. Owing to factors beyond our control during application, recommendations given in this data sheet require tests and experiments by the customer. Our recommendations do not exempt the customer from the obligation to check any infringements of third-party rights himself and eliminate them if necessary. The suggestions for product use are not equivalent to a warranty of its suitability for the recommended purpose.

Each new release of this data sheet supersedes the previous one.